



Shenzhen Xinhe'an Technology Co., Ltd.

xhafiresafety.com



Smart RS485 Photoelectric Smoke Detector with Relay Output - Efficient Fire Alarm Solution for Building Security

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: XHA
- Certification: CE
- Model Number: CA2001N
- Minimum Order Quantity: 1
- Price: negotiable
- Packaging Details: 100pcs/carton
- Delivery Time: 3 Working days
- Payment Terms: T/T, Western Union
- Supply Ability: 10000PCS/Month

RS485 Smoke Detector

ODM/OEM

DC12-24V

485 Protocol



Product Specification

- Highlight: White 4 Wire Smoke Detector, 24V Smoke Detector Wi
- Alarm Current: $\leq 5\text{mA}$
- Static Current: $\leq 5\text{mA}$
- Contact Capacity: 1A DC24V (No/Nc Optional)
- Output: Sound & Light Alarm, Relay Output
- Rated Operational Voltage: DC12~24V
- Sound Pressure Level: Above 65dB
- Humidity: $\leq 95\%$
- Work Temperature: $-10^\circ\text{C} \sim +50^\circ\text{C}$
- Size: 96*49mm(Diameter * Thickness)



Product Description

DC12/24V Industrial Control Equipment Fire Alarm Smoke Detector



Introduction

4-Wire smoke alarm with relay output is common used for industrial control equipment, power cubicle, charging pile, alarm bell etc fire warning system. This smoke alarm has the characteristics of high sensitivity, stability and reliability, small power consumption and durability. Easy to install.

Parameters

Product Name	smoke detector with relay output	Rated operational voltage	DC12~24V
Sound pressure level	≥65db	Static current	≤300uA
Alarm current	≤90mA	Work temperature	-10°C~+50°C
Output	Sound&light alarm, relay output	Humidity	≤95%.
Product standard	CE	Dimension	Φ105mm,H50mm

Functions

Work : Under normal circumstances, the indicator of the detector will flash about every 8 seconds. When the smoke concentration reaches or exceeds the alarm value, the red LED light of the detector remains bright,

makes a sound, and starts the relay output.

When the smoke concentration in the environment returns to normal state, the detector automatically returns to normal state (Alarm can automatically restore the state).

Installation

The mounting hole size of the detector base is 49mm - 64.2mm. During installation, two installation holes with a diameter of 5 mm were punched at a suitable position on the ceiling.

Smoke detectors are not suitable for use in :

- A. Places where smoke is normally held ;
- B. where there are large dust, water mist, steam, oil mist pollution and corrosive gas ;
- C. ventilation speed is greater than 5m / s.

Product range

Conventional Fire Alarm System

Addressable fire alarm system

Gas Extinguishing control system



Beam Detector

4 wire smoke detectors with relay output.

2 wire Conventional smoke and heat detectors

Explosion-proof flame detector for fire alarm system

Standalone smoke detectors and combustable gas detector



Service

1. OEM &ODM service.
2. Provide technical support and after-sale service.
3. 1 year warranty.
4. Normally 15 working days lead time.
5. Welcome sample order.



 +8615986702194 Claire.tian@xinheantech.com xhafiresafety.com

406,Jude Building,Zhengfeng South Road,Fuyong Street,Bao'An District, Shenzhen City, Guangdong Province.
China,518103